IN THE CLAIMS:

1-27. **(Canceled)**

28. (Currently Amended) An X-ray system including an X-ray emitter and an X-ray-sensitive camera for the creation of dental X-ray images, said camera including a first and a second image detector, said first image detector being provided for the creation of a panoramic tomographic image of upper and lower jawbones of a patient and said second image detector being a face sensor for the creation of a 2D image, and including means for the creation of 3D images of a subvolume of a mandibular arch of the patient, which means create several 2D images from different directions and compute a 3D image therefrom using cone beam technology with associated reconstruction algorithms, and including adjustment means for adjusting at least one of said camera, and/or-said second image detector, and/or said X-ray emitter and/or a primary diaphragm and/or combinations thereof such that said second image detector present in said camera is positioned in an optical ray path of said X-ray emitter, and including an installation for the creation of teleradiographic images with another image detector and, when said X-ray emitter is aligned for the creation of a teleradiographic image, said camera is disposed in the region of the optical ray path between said X-ray emitter and said image detector

Amendment dated June 15, 2009 Reply to OA of Jan. 13, 2009 Serial No. 10/550,600

of said installation for the creation of teleradiographic images and is radiolucent in said region.

29. (Currently Amended) An X-ray system including an X-ray emitter and an X-ray-sensitive camera for the creation of dental X-ray images, said camera including a first and a second image detector, said first image detector being provided for the creation of a panoramic tomographic image of upper and lower jawbones of a patient and said second image detector being a face sensor for the creation of a 2D image, and including means for the creation of 3D images of a subvolume of a mandibular arch of the patient, which means create several 2D images from different directions and compute a 3D image therefrom using cone beam technology with associated reconstruction algorithms, and including adjustment means for adjusting at least one of said camera, and/or said second image detector, and/or said X-ray emitter and/or a primary diaphragm and/or combinations thereof such that said second image detector present in said camera is positioned in an opticala ray path of said X-ray emitter, and including an installation for the creation of teleradiographic images with another image detector and the path of adjustment is such that, when the X-ray emitter is aligned for the creation of a teleradiographic image, said camera is moved out of the optical path between said X-ray emitter and said

Amendment dated June 15, 2009 Reply to OA of Jan. 13, 2009 Serial No. 10/550,600

image detector of said installation for the creation of teleradiographic images.

30. **(Canceled)**

31. (Currently Amended) An X-ray-sensitive camera, comprising a casing, a first X-ray-sensitive image detector for the creation of a tomographic image in said casing, a second X-ray-sensitive image detector for the creation of plane images in said casingand wherein the two image detectors are disposed in a common casing, and said second image detector is disposed alongside said first image detector, and including adjustment means for the purpose of causing, as desired, said first image detector or said second image detector to assume correct alignment relative to an X-ray emitter for the creation of the respective X-ray image, wherein said second image detector is disposed on a rear side of said first image detector.

32. **(Canceled)**

33. (Currently Amended) TheA camera as defined in claim 31, wherein said adjustment means and the two image detectors are housed in a common casing of said camera.

34. (Currently Amended) TheA camera as defined in claim 33, wherein said adjustment means are provided on said casing of said camera and in a region of connecting means for the attachment of said camera to a support and said camera is variably displaced, as an entity, relatively to said connecting means.

35. (Canceled)